

# LOTUS EUROPA S.2

## Technical Specification

### BODY/CHASSIS

One piece moulded glassfibre reinforced plastic, fully sound-proofed and fitted with safety glass all round. Separate rust-proofed steel backbone chassis. Rear mounted engine and transmission. Luggage compartments front and rear with total capacity  $7\frac{1}{2}$  cu. ft.

### SUSPENSION

All independent suspension, front wheel disc brakes, drum rear, radial ply high speed tyres on wide base ventilated steel wheels. Rack and pinion steering.

### ENGINE

1564 c.c. all aluminium overhead valve four cylinder unit. Double choke carburettor. 87 b.h.p. at 6,000 r.p.m.

### TRANSMISSION

Four speed all synchromesh close ratio gear box with 3.56:1 final drive. 18.3 m.p.h. (29.3 k.p.h.) per 1,000 r.p.m.

### INTERIOR

Carpeted and sound-proofed interior, mahogany facia with complete G.T. instrumentation. Fully adjustable seats with integral headrests, electric windows, glove locker and two map pockets. Heater, seat belts, windscreen washers and variable speed wiper as standard. Full Lotus "Airflow" ventilation with twin variable face-level vents.

### DIMENSIONS

Length: 13 ft.  $1\frac{1}{4}$  ins. Height: 43 ins. Weight from 1,350 lbs. Width: 64 $\frac{1}{2}$  ins.

